



**GENERAL SPECIFICATIONS**

Features	Single side monochrome or color
Input feeder	65 (ISO CR-80-ISO 7810: 54x86mm)
Output hopper	50 (ISO CR-80-ISO 7810: 54x86mm)

**OPERATING SYSTEMS**

Windows 2000/NT 4.0 and XP

**COMMUNICATIONS INTERFACE**

Software	Rainbow included
Serial port	Yes
Parallel port	Yes
USB	Ready
Ethernet	Ready

**MEMORY**

Resident memory	4 MB color and 2 MB monochrome
-----------------	--------------------------------

**COLOR PRINTING SPECIFICATIONS**

Printer technology	Dye sublimation/Thermal transfer
Print speed full color	90 CPH (40 sec/card)
Print speed monochrome	600 CPH (6 sec/card)
Printhead resolution	11,8 dots/mm 300 dpi
Edge to edge	Yes

**CARD SPECIFICATIONS**

Card types	PVC, ABS, PET
Thickness	0,40 - 0,76mm (ISO) - 0.15" - 0.30"

**MECHANICAL**

Printer size	Width: 250mm/12 3/8" (450mm/18" with hopper) Depth: 220mm/8" - Height: 350mm/10"
Weight	6 kg/13 lbs

**ENCODING OPTIONS**

Magnetic Stripe ISO	Yes 3 track (Hi-Co and Lo-Co)
---------------------	-------------------------------

**BAR CODES**

Code 39, Code 128 B&C; with & without check digit; 2 of 5 interleaved; EAN 8 & EAN 13

**ENVIRONMENTAL**

Operating temperature: 5-35° C (60°F to 86°F)  
Ventilation: cooling fan for the thermal printhead

**EXTERNAL POWER SUPPLY**

100-240 volts AC, 50/60 Hz

**MODELS**

DILPHIN C/CM/MONO/MONO M  
C=color; MONO=monochrome; M=magnetic encoder



CIM S.p.A. - Via O. Serra, 2  
40012 Calderara di Reno (BO) - Italy  
Tel. +39 051 6465011 - Fax +39 051 6465012  
info@cimitaly.it - www.cimitaly.it  
www.dolphinprinter.com



Access Control



Card Keys



Club Membership



absolut

Rev. 01 - 01/04

THE DOLPHIN EVENT:  
CARD PRINTING BECOMES SMART!

